

lubemate TM
by macnaught

PRODUCT CATALOGUE

LUBEMATE® EQUIPMENT

Macnaught proudly launched Lubemate® to provide the market with products that deliver value for every day jobs. Over the years, Lubemate products are exposed to the same testing and quality assurance processes, offering products that have been selected based on Macnaught's fuel, fluid and lubrication application and technical product knowledge.

The Lubemate range features equipment suitable for common grease, oil, fuel applications and hose reels. Lubemate® products are selected by Macnaught to ensure that they are fit for purpose. Lubemate products are backed by a Macnaught warranty of up to 2 years*.

* Note: Subject to Macnaught warranty terms and conditions see [macnaught.com/warranty](https://www.macnaught.com/warranty)

GREASE EQUIPMENT

18V RECHARGEABLE GREASE GUN

L-BG18V (NiCad) | L-BG18VLI (Li-Ion)

- Includes 1m flexible extension & 4-jaw coupler
- Battery charger, spare battery and shoulder strap in a hard carry case
- Delivers up to 50g/min in free flow
- Suitable for 450g grease cartridge



AIR OPERATED GREASE GUN

L-AG450

- 40:1 Ratio air operated grease gun
- 450g cartridge or bulk fill
- 300mm high pressure hose & 4-jaw coupler
- Develops 33,100kPa (4,800psi)
- Suitable for greases up to NLGI 2



MINI-PISTOL GREASE GUN

L-MPG

- For use with 3oz. cartridge or bulk fill
- 100mm steel extension & 4-jaw coupler
- Develops 24,000kPa (3,500psi)
- Delivers 0.4g per shot
- Suitable for greases up to NLGI 2



PISTOL-GRIP GREASE GUN PREMIUM

L-PG450PV

- 450g or bulk fill
- Delivers up to 48,300kPa (7,000psi)
- Filler/bleed valve
- 300mm high pressure flexible extension & 4-jaw coupler
- High pressure/volume setting



LEVER-ACTION GREASE GUN

L-LG450

- 450g or bulk fill
- Rigid extension & 4-jaw coupler
- Develops up to 69,000kPa (10,000psi)



GREASE EQUIPMENT

AIR OPERATED GREASING KIT

L-GK20 (20kg) | L-GK180 (180kg)

- 50:1 Ratio pump
- Flowrate: 700g/min
- Suitable for greases up to NLGI 2
- Supplied with air-line lubricator



GREASE NIPPLE KITS



AGRICULTURAL KIT 110 PIECES

L-NP110AG

More suited to a mixed fleet situation where imperial & metric sizes would be encountered.

IMPERIAL KIT 50 PIECES

L-NP50B

This kit is purpose designed for situations where older or US sourced equipment is deployed.

METRIC KIT 101 PIECES

L-NP101M

Appropriate where either a late model fleet or European or Japanese sourced equipment is used.



SAE/NPT KIT 80 PIECES

L-NP80S

This kit suits predominately older type US sourced equipment.

METRIC KIT 80 PIECES

L-NP80M

Suited for a more modern fleet where European or Japanese sourced equipment is found.

GREASE ACCESSORIES

FLEXIBLE EXTENSION

L-FX18 (450mm) | **L-FX12** (300mm)

- Working pressure up to 40,000kPa (5,800psi)
- Burst pressure up to 95,000kPa (13,775psi)



4 JAW COUPLER L-C4

4 jaw coupler
up to 6000psi



360° SWIVEL L-ZS

1/4" BSPT(F) x 1/4" BSPT(M)
fluid inlets



GREASE CONTROL VALVE L-GCV

Used with air operated
equipment for grease delivery.

OIL EQUIPMENT

NEW

20L PREMIUM OIL PUMP L-DP20P

- "D" handle grip for easy downstroke operation
- Suitable for oils up to SAE 140/ISO680 viscosity
- Used for engine oils, gear oils, diesel and light fuel oil, antifreeze, glycerin
- Suits between 20-25L drums via suction tube extender



LEVER-ACTION BARREL PUMP L-LBP

- 500mL per stroke
- Lever operated pump
- Suitable fluids: diesel, kerosene, lubricating oils to SAE 90 and service fluids
- Telescopic suction tube 60-205L



20L ATF/GEAR OIL PUMP L-SOP20

- Spring pump provides automatic dispensing of engine and gear oils
- Delivers up to 340mL per stroke
- Suitable for oils up to SAE 140 viscosity
- 1.5 metre anti-kink hose with trigger nozzle
- Fits 20L drums



60L ATF/GEAR OIL PUMP L-SOP60

- Spring pump provides automatic dispensing of engine and gear oils
- Delivers up to 500mL per stroke
- Suitable for oils up to SAE 140 viscosity
- 1.5 metre anti-kink hose with trigger nozzle
- Fits 60L drums



OIL EQUIPMENT

240V OIL TRANSFER PUMP L-OTP240V

- Flow rate up to 40LPM (free flow)
- Suitable for oils up to SAE 250 viscosity
- Self-priming rotary gear pump, equipped with a built-in bypass valve



AIR OPERATED OIL PUMP 1:1 L-ARPD1

- Suitable for oils and fluids up to SAE 140 viscosity
- Delivery output up to 40LPM, depending on viscosity
- Supplied with air-line lubricator

Also available:

L-ARPD1-KIT1: Oil Bar Kit - L-ARPD1 supplied with oil bar tap, jug and fittings.



L-ARPD1



L-ARPD1-KIT1

AIR OPERATED OIL PUMP 3:1 L-ARPD3

- Suitable for oils and fluids up to SAE 140 viscosity
- Delivery output up to 14LPM, depends on viscosity
- Supplied with air-line lubricator

Also available:

L-ARPD3-KIT2: L-ARPD3 supplied with metered oil gun. Supplied with drum wrench, delivery hose and fittings.

L-ARPD3-KIT3: L-ARPD3 supplied with unmetered oil gun. Supplied with drum wrench, delivery hose and fittings.



L-ARPD3



L-ARPD3-KIT2

OIL EQUIPMENT

DIGITAL CONTROL GUN FLEXIBLE EXTENSION L-MOGF

- Measures oil delivery coming from air operated oil pumps directly into engine or other equipment
- Supplied with flexible extension & manual non-drip nozzle
- Flow rates up to 30LPM
- Maximum working pressure: 6,900kPa (1000psi)
- Fluid inlet: 1/2"BSP (F) Swivel



OIL CONTROL GUN FLEXIBLE EXTENSION TD-01

- Supplied with flexible extension & manual non-drip nozzle
- Flow rates up to 30LPM
- Maximum working pressure: 6,900kPa (1000psi)
- Fluid inlet: 1/2"BSP (F) Swivel



OIL EQUIPMENT

VACUUM WASTE OIL DRAINER L-OD90 (90L)

- ✔ Gravity and air operated waste oil drainer
- ✔ Maximum vacuum pressure: 0.85bar
- ✔ Draining oil speed: 1.8 - 3LPM
- ✔ Suitable for draining waste oil from engines, gear boxes and differentials of all vehicles
- ✔ Vacuum gauge for checking suction power
- ✔ Holds vacuum for up to 24 hours



WASTE OIL EXTRACTOR L-OE6 (6.5L)

- ✔ Suitable for extracting all types of oils as well as water based fluids
- ✔ Powerful pump creates a vacuum so continuous pumping is not necessary
- ✔ Supplied with 3 suction probes



OIL SUCTION GUN L-SG500 (500mL)

- ✔ Transfer of lubricating oils in and out of sealed compartments
- ✔ Suitable for all types of engine, gear & transmission oils or non-corrosive service fluids



OIL ACCESSORIES

TOP-UP PUMP
L-TUP1L (1L)



2" DRUM FAUCET WITH SIGHT GLASS
L-DTP2



WALL MOUNT DRIP TRAY
L-WMDT



ANTI-SPILL FUNNEL
L-ASFS (1.7L)
L-ASFL (3.0L)



PORTABLE FUEL FILTER FUNNEL
Removes water from Fuel
L-PFFL



UNIVERSAL CLAMP FUNNEL
L-UCFL



FUEL & OIL FUNNEL
L-FOFL



DRUM TROLLEY
L-DT2060



OIL CAN
L-OC300 (300mL)



OIL BAR TAP PUMP MOUNT
L-OBTP



PLASTIC JUG
L-J2L (2L) | L-J5L (5L)
L-J6L (6L) | L-J8L (8L)

FUEL EQUIPMENT

BI-LOBE FUEL PUMP L-BLPH

- Flow rate up to 100LPM
- Suitable for diesel, kerosene and light viscosity oils up to SAE 30
- Pump in both directions
- Fits 60–205L containers



NEW

ROTARY VANE PUMP (STAINLESS STEEL) L-SSRP

- For use with 205L drums
- Delivers up to 4L per 20 turns
- Suitable for use with water based media, antifreeze, acids, chemicals, all petroleum based products, lacquer, thinner, Urea, and DEF



ROTARY VANE FUEL PUMP WITH HOSE L-RPH

- Delivers up to 20LPM (250mL per rev)
- Suitable for diesel, kerosene and mineral oils up to SAE 90



NEW

STAINLESS STEEL DRUM PUMP L-SSHP

- Drum Size: 50-205L drums
- Delivery up to 600ml per stroke
- Suitable for use with solvents, diesel, kerosene, thinners, acetone, benzene, naphtha, Urea, DEF, light oils (up to SAE 40) and water



FUEL EQUIPMENT

240V AUTO MINI BOWSER L-HMBA240V

- Flow rate up to 80LPM (free flow)
- Suitable for diesel and kerosene
- Nozzle holder in cabinet has built-in on/off switch
- 240V AC pump unit
- 4-digit mechanical flow meter
- 8-digit accumulative total
- Supplied complete with 4-digit mechanical meter, power cable, suction, delivery hose and strainer



12V DIESEL PUMP KIT L-FPA12V (Auto Nozzle)

- Flow rate up to 40LPM (free flow)
- Suitable for diesel use only
- 30min duty cycle
- 12V pump unit with carry handle supplied with 2m power cable, alligator clips and nozzle
- Pump not sold separately



L-FPM12V (Manual Nozzle):
12V Diesel Pump Kit



12V HIGH FLOW DIESEL PUMP KIT L-HFFPA12V (Auto Nozzle)

- Flow rate up to 56LPM (free flow)
- Suitable for diesel use only
- 30min duty cycle
- 12V DC pump unit
- Supplied with power cable with alligator clips, delivery/suction hose (cut to suit length) and nozzle
- Pump not sold separately



L-HFFPM12V (Auto Nozzle):
12V High Flow Diesel Pump Kit



FUEL EQUIPMENT

19.2V BATTERY DRUM PUMP L-BDP205L

- ✔ Suitable for diesel, Urea/ DEF, water, kerosene, antifreeze, windshield washer fluid, mild detergents, agricultural chemicals and light oils up to SAE 10
- ✔ 19.2V 1.5Ah Li-Ion battery for extended battery life
- ✔ Manual nozzle
- ✔ Suits IBC or 205L drums
- ✔ Note: Not suitable for petrol



CHEMICAL ROTARY PUMP L-MACP200

- ✔ Suitable for transferring mineral oils, acids, alkalis, alcohols, diesel, coolants, water-based chemicals and clean or salt waters. AdBlue/DEF compatible (check compatibility)
- ✔ Flow rate up to 20LPM (viscosity dependent)
- ✔ Compatible with 60-205L drums (3 additional bung adaptors)



PLASTIC SYPHON PUMP L-PSP

- ✔ Polyethylene pump for diesel or water-based fluids
- ✔ Wetted materials - polyethylene and PVC
- ✔ For use with 205L drums
- ✔ Supplied with flexible delivery hose
- ✔ Dispenses 21LPM



BATTERY OPERATED PLASTIC PUMP L-BOP-5

- ✔ Suitable for transfer of diesel, kerosene, light oils and water
- ✔ Flow rate up to 7LPM (1.8 GPM)
- ✔ For use with: 20L / 5 gallon drums
- ✔ Uses 2 x standard "D" size Alkaline batteries (not included)



FUEL EQUIPMENT

NEW 240V UREA/DEF TRANSFER PUMP L-SSUP240V

- ✔ Suitable for use with DEF, Urea, antifreeze, detergents, soap, windshield fluid and water
- ✔ 240V Self-priming Stainless Steel rotary vane pump
- ✔ Flow rate 56LPM
- ✔ Continuous duty cycle
- ✔ Maximum current draw: 1.5A with IP54 motor protection
- ✔ Inlet / outlet: 3/4" BSPP (F)
- ✔ Maximum suction lift : 1m



240V UREA/DEF IBC TRANSFER KIT L-UPM240V

- ✔ Flow rate up to 25LPM
- ✔ Suitable for Urea/DEF and water
- ✔ Continuous duty cycle
- ✔ Supplied with manual nozzle, delivery hose, power cable suction tube and digital turbine meter (L-DTUM)
- ✔ 240V pump unit



AIR OPERATED DIAPHRAGM PUMPS

Ideal for dirty fluid transfer, these pumps provide continuous flow for use with waste and clean oil, diesel, engine coolant and water

L-DDP13 (1/2")

- Flow rate up to 45LPM
- Inlet/Outlet: 1/2" BSP (F)
- Maximum air pressure: 116psi (8bar)
- Maximum allowable particle size: 1/8"



L-DDP19 (3/4")

- Flow rate up to 60LPM
- Inlet/Outlet: 3/4" BSP (F)
- Maximum air pressure: 116psi (8bar)
- Maximum allowable particle size: 1/8"



L-DDP25 (1")

- Flow rate up to 90LPM
- Inlet/Outlet: 1" BSP (F)
- Maximum air pressure: 116psi (8bar)
- Maximum allowable particle size: 1/8"



FUEL EQUIPMENT

DIGITAL METERS

L-DTFM (Diesel/Kerosene) | **L-DTUM** (Urea/DEF)

- Flow range: 10 – 100LPM
- Inlet/Outlet: 1" BSP (F)
- Maximum operating pressure: 72psi (5bar)
- 5-digit resettable totaliser
- 7-digit non-resettable totaliser
- Field calibratable
- IP55 protection



MECHANICAL DIESEL METER

L-FM25

- Flow range: 20 – 120LPM
- Nutating disc
- Inlet/Outlet: 1" BSP
- 4-digit resettable totaliser
- 8-digit non-resettable totaliser
- Register can be rotated



FUEL ACCESSORIES

FUEL NOZZLE AUTOMATIC – ULP L-FNAU

- ULP automatic shut off nozzle
- 3/4" BSP (F) inlet
- 13/16" o.d. spout



FUEL NOZZLE MANUAL – ULP L-FNMU

ULP manual nozzle.
3/4" BSP (F) inlet. 13/16"
o.d. spout



DIESEL NOZZLE AUTOMATIC – HI-FLO L-ANHF

Hi-flo automatic fuel nozzle for
diesel. 1" BSP (F) inlet. 1" o.d.
spout. Up to 120LPM flow rate,
depending on installation



SWIVEL NOZZLE – 3/4" X 1" ASB1925

3/4" BSPT (M) x 1" BSPT (F)

FUEL NOZZLE AUTOMATIC – DIESEL L-FNAD

- Diesel automatic shut off nozzle
- 3/4" BSP (F) inlet
- 15/16" o.d. spout



FUEL NOZZLE MANUAL – DIESEL L-FNMD

Manual fuel nozzle for diesel.
1" BSP (F) inlet. 15/16"
o.d. spout



SWIVEL NOZZLE – 3/4" L-FS19

Straight type swivel for fuel
nozzles with 3/4" fluid inlet.
3/4" BSP (M) x 3/4" BSP (F)



DIESEL NOZZLE MANUAL – HI-FLO MNHF-01

Hi-flo manual nozzle for diesel.
1 1/2" BSP (F) inlet



SWIVEL NOZZLE – 1" L-FS25

Straight type swivel for fuel
nozzles with 1" fluid inlet.
1" BSP (M) x 1" BSP (F)

HOSE REELS



- Positive hose latch – locks yours hose at any length
- Easy to carry – a convenient handle makes the reel easily portable
- Built-in hose layering mechanism – hose rewinds safely with no bunching or kinks
- 180° Swivel bracket – the hose follows your direction as you move around
- UV Stabilised hose and case – the hose is ready for Australia's toughest environmental conditions

AIR/WATER REEL

L-PAW1030 (10mm x 30m)

L-PAW1220 (12mm x 20m)



MINI AIR/WATER REEL

L-PAW1014 (10mm x 14m)



DOMESTIC WATER REEL

L-PDW1225 (12.5mm x 25m)



lubemate [™]
by macnaught

Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205.
Australia **Ph:** 1800 185 102 **Fax:** +61 2 9597 7773 **Email:** info@macnaught.com.au **Website:** macnaught.com


macnaught
Built to last since 1948.