



AUTOMOTIVE SOLUTIONS



R3 HOSE REELS

AR320R-01 COMPRESSED AIR REEL 20M X 3/8"

- Premium PVC hose
- Maximum working pressure 275 psi

GR215K-01 GREASE REEL 15M X 1/4"

- SAE100R2 hydraulic hose
- Maximum working pressure 5000 psi

OMP415B-01 OIL REEL 15M X 1/2"

- SAE100R17 hydraulic hose
- Maximum working pressure 1000 psi



**F-SERIES
HEAVY DUTY
TWIN PEDESTAL
OIL REEL
HO1915-01**

- Twin pedestal hose reel
- 15m x 3/4" Oil hose and BSP fittings
- Maximum working pressure 1450 psi



**E-SERIES ENCLOSED
HOSE REELS
ESAW1210-01**

- 10m x 1/2" Standard Air Hose
- Maximum working pressure 200 psi

ESO1210-01

- 10m x 1/2" Oil hose
- Maximum working pressure 1000psi



RELIABLE AND FIT FOR PURPOSE HOSE REEL SOLUTIONS



**COMPRESSED
AIR / WATER REEL
L-AWP1030**

- 30m x 3/8" PVC hose
- Maximum working pressure 300 psi



**TWIN PEDESTAL
HOSE REELS**

- L-AWTP1215**
15M X 1/2" AIR/WATER
- L-AWTP1920**
20M X 3/4" AIR/WATER

L-DTP2515
15M X 1" DIESEL

- Maximum working pressure 290 psi



ENCLOSED METAL HOSE REELS



EK SERIES

The narrow form of the EK-Series offers a reliable and fit for purpose solution with maximum hose length capacities for your service bay fluid handling.



**SLEEK AND DURABLE ENCLOSURE
- DESIGNED FOR MINIMUM PROFILE**



EL SERIES

The narrow form of the EL-Series is designed for the smallest possible wall or gantry spaces.



**HIGH QUALITY HOSE AND FITTINGS
- EXCEEDS REQUIRED STANDARDS**

L-EKAW1015	15M X 3/8" Air / Water Hose & BSB Fittings (300psi)
L-EKAW1215	15M X 1/2" Air / Water Hose & BSB Fittings (300psi)
L-EKG0615	15M X 1/4" Grease Hose & BSB Fittings (5800psi)
L-EKG1015	15M X 3/8" Grease Hose & BSB Fittings (4785psi)
L-EK01215	15M X 1/2" Oil Hose & BSB Fittings (2320psi)

L-ELAW1015	15M X 3/8" Air/Water Hose & BSB Fittings (300psi)
L-ELAW1210	10M X 1/2" Air/Water Hose & BSB Fittings (300psi)
L-ELG0615	15M X 1/4" Grease Hose & BSB Fittings (5800psi)
L-EL01210	10M X 1/2" Oil Hose & BSB Fittings (2320psi)

MINILUBE®



GREASING SYSTEM K7-24

- Up to 0.45g per shot (high pressure setting)
- Up to 1.25g per shot (high volume setting)
- Maximum viscosity: Up to NLGI 2
- 2.5kg pump system with KT5 container included



POWERLUBE®



P3 GREASING SYSTEM - 20KG P3-01C

- 50:1 Ratio Pump
- KY Supergrip Coupler
- ZSB high pressure swivel
- Supplied with pump, lid, follower, 4m high pressure grease hose and B2 Booster gun



P58 MAXILUBE HEAVY DUTY AIR OPERATED GREASE SYSTEM P58PGLF-01

- Delivery pressure up to 59,900 kPa (8700 psi)
- Maximum viscosity: Up to NLGI 2
- Supplied with pump, lid, follower, 2.5m grease hose and B2 Booster gun



POWERGUN



GREASING SYSTEM PG450

- Dispense up to 12x grease cartridges per charge free flow
- Supplied with 2x18V 3.0Ah Lithium-ion Rechargeable Battery Packs and Charger
- Supplied with 1m long flexible extension and KY Supergrip Coupler



FLEXIGUN®



450G GREASE GUN K29-01

- Delivery pressure up to 68,900 kPa (10,000 psi)
- Up to 0.68g per shot
- Maximum viscosity: Up to NLGI 2
- Supplied with 300mm flexible extension and KY Supergrip Coupler



LEVERGUN®



450G LEVER GUN K45-01

- Delivery pressure up to 82,750 kPa (12,000 psi)
- Up to 1.5g per shot
- Maximum viscosity: Up to NLGI 2
- Supplied with 150mm steel extension and KY Supergrip Coupler



**BEST
SELLER**



← 1.3" (34mm) →



← 2.5" (64mm) →

**QUICKER
EASIER
SAFER**

- Patent approved smart release mechanism enables effortless one handed release & pull
- Up to 10,000psi

Part Number	Description
KYPLUS-01	KYPLUS Grease Coupler- BSP
KYPLUS-02	KYPLUS Grease Coupler - NPT
KYPLUS-03	KYPLUS Grease Coupler - M10X1
KYPLUSXL-01	KYPLUSXL Long Grease Coupler - BSP
KYPLUSXL-02	KYPLUSXL Long Grease Coupler - NPT
KYPLUSXL-03	KYPLUSXL Long Grease Coupler - M10X1





**HEAVY DUTY
TROLLEY BASED OIL
DISPENSING SYSTEM
OS100GE-01**

- Kit supplied with R-Series 3:1 ratio pump, Metered oil control gun, 205 L Drum Trolley & Retractable Oil Reel 1/2" x 15m.



lubemate
by macnaught

**MEDIUM DUTY
TROLLEY BASED OIL
DISPENSING SYSTEM
L-ARPTR-1**

- Kit supplied with 3:1 ratio pump, Metered oil control gun, 205 L Drum Trolley & Retractable Oil Reel 3/8" x 10m.



**1:1 'R' SERIES AIR
OPERATED OIL
PUMP DRUM
R100T-01**

- 1:1 ratio pump
- Flowrate delivery up to 60 L/min
- Supplied with suction tube & 2" bung adaptor to suit 205 L containers



**5:1 'T' SERIES AIR
OPERATED OIL PUMP
T512T-01**

- 5:1 Ratio Pump
- Flowrate – up to 11 L/min (free flow)
- Supplied with suction tube & 2" bung adaptor to suit 205 L containers



**ROTARY VANE
PUMP
RVP-01**

- Suits both 205 & 60 L drums via sliding bung adaptor
- Delivers up to 20 L/min (in both directions)
- Suitable for Diesel, Kerosene and Oils up to SAE90



**ALL PURPOSE
OIL TRANSFER
PUMP
MAOP20**

- Suits 15-25 L containers
- Easy to prime pump
- Additional bung adaptors
- Suction Tube Extender
- Delivers up to 75 ml per stroke, viscosity dependant



**MULTI-PURPOSE
GEAR OIL PUMP
C7-01**

- Compatible fluids - Kerosene, Two Stroke Mix, Lubricating Oils up to SAE140
- Pump output: 100 ml/stroke
- Compatible with most drum sizes from 15-25 L



**OIL CONTROL GUN,
ELECTRONIC
FLEXIBLE
EXTENSION
HG20F-012E-01**

- Fitted with digital meter
- Suitable for oils up to SAE140
- 1/2" BSPT inlet
- Automatic non-drip nozzle



**OIL CONTROL GUN,
RIGID EXTENSION
HG20R-01**

- Max pressure up to 6,900 kPa (725 psi)
- Flow rate up to 30 L/min
- 1/2" BSPT inlet
- Automatic non-drip nozzle



**OIL CONTROL GUN
WITH FLEX
EXTENSION AND
AUTO NOZZLE
L-0GFA**

- Max pressure up to 10,000 kPa (1450 psi)
- Flow rate up to 35 L/min
- 1/2" BSP (F) inlet
- Automatic non-drip nozzle

lubemate
by macnaught



**DIGITAL OIL GUN
WITH FLEX
EXTENSION AND
AUTO NOZZLE
L-DOGFA**

- Fitted with digital meter
- Max pressure up to 5,000 kPa (725 psi)
- Flow rate up to 35 L/min
- 1/2" BSP (F) inlet
- Automatic non-drip nozzle



OTHER CONTROL GUNS ALSO AVAILABLE

BOP

BATTERY OPERATED PUMP

BATTERY OPERATED PUMP

Simple yet clever, the BOP is a portable, rechargeable, 18V battery operated oil pump, designed to improve workshop efficiency & reduce workshop fatigue inherent with operating manual oil pumps.



GOOD DESIGN AWARD WINNER



2 YEARS MACNAUGHT WARRANTY



- Easy Portable Power Head
- Lithium-ion Battery and Charger
- Drainback Adapter
- New Modular Concept
- Adjustable Suction Tube



- Easy Control Dispensing Gun
- 1.5m Hose



BOP INLINE METER IM012EB-01

- Flow Range: up to 10l/m
- Operating Temp: -20°C to 70°C
- Operating Pressure: 20psi (MAX 60psi)

Product	Contents	Product Code
20L Starter Kit	Pump Stem, Power head, Hose & Gun assembly, Battery Pack and Charger	BP20S-UNA
20L Pump Stem Kit	Pump Stem, Hose & Gun assembly	BP20X-UNA
60L Starter Kit	Pump Stem, Power head, Hose & Gun assembly, Battery Pack and Charger	BP60S-UNA
60L Pump Stem Kit	Pump Stem, Hose & Gun assembly	BP60X-UNA
Inline Meter	BOP Inline Meter, Fittings & Battery	IM012EB-01
Power head	Battery Operated Power head to suit Pump Stem	BP20-PH
Battery	18V2.0Ah Rechargeable Battery	BPB-20AH
Charger	Charger suited for 2.0Ah Battery	BPC-A



THE OIL MANAGEMENT SYSTEM

by **lubemate**™
by macnaught



STEP 1 Select your oil can size



Oil Cans available in 3 sizes - 3L, 5L and 10L.
Oil Cans are see-through to make it easy to see oil levels when in use.

STEP 2 Select your rings and labels from 5 Colours



Oil Drum Rings and Labels are colour coded for easy fluid identification

STEP 3 Select your lid from variety of spouts and lids



The lids have an easy hold handle and securely fit to the Lubemate Oil Can

To reach into difficult and tight areas



These extensions fit the stretch spout lids to give you a flexible extension

VISIT MACNAUGHT.COM FOR FULL RANGE OF ACCESSORIES



AIR OPERATED DIAPHRAGM PUMP - 1"

DDP25

- 690 kPa max air pressure (100 psi)
- Suitable for oils (new & used), Engine Coolants RTU (new & used), oily water, diesel
- Flow rates up to 174 L/min (free flow) viscosity dependent



IDEAL FOR MOBILE WASTE EVACUATION APPLICATIONS



MANUAL WASTE OIL EXTRACTOR 6.5L

L-OE6

- Suitable for extracting all types of oils as well as water based fluids
- 6.5 L reservoir capacity
- Up to 15 strokes to create powerful vacuum



WASTE OIL DRAINER 90L

L-OD90

- Pneumatic & Gravity
- 90 L Capacity
- Wide bowl extender with filter mesh
- Extends up to 1.85m
- Oil bowl diameter 400mm



TRUCK WASTE OIL DRAINER STANDARD 95L

L-TOD95

- Low level oil drainer with swivel castors for easy movement
- Large 95 L capacity



RECHARGEABLE LED INSPECTION LIGHT

WL-IL400

- Main Light: Max. 400 Lumens
- Runtime: Main light 3.5 hrs, Top Light 12 hrs
- 2 x Adjustable Hooks
- 2 x Strong Magnets



RECHARGEABLE LED POCKET FLOOD LIGHT

WL-FL1400

- 1400 Lumens at 120° dispersed range
- 3 Brightness Levels
- Super Strong Magnet on the handle for rigid placement



RECHARGEABLE MULTI-FUNCTION WORK LIGHT SET

WL-SET350

- Max Output 350 Lumens
- Up to 8.5hrs run time
- Torch body has a magnetic base



RECHARGEABLE LED UNDERHOOD LIGHT

WL-UH1500

- Main Light: Max. 1500 Lumens
- Adjustable length extending 350mm on each side
- 360° swivel hooks at the end



GET IN TOUCH



AU CUSTOMER SERVICE
1800 185 102
orders@macnaught.com.au



NZ CUSTOMER SERVICE
0800 023 510
nzorders@macnaught.com.au



Scan me for more information

CONNECT WITH US!



Find us on socials @macnaught

macnaught.com