



BOP 60/205L DEF/UREA

Designed in Australia, the Macnaught BOP is a portable and rechargeable 18 Volt battery operated pump, designed to improve workshop efficiency and reduce fatigue with the flick of a switch. The BOP Powerhead can be transferred across multiple pump stems, for either 20 or 60/205 litre drums. The on-demand flow nozzle allows full control over fluid delivery with flow rates up to 7L/min.











Suitable For	BOP 60/205 Litre DEF/Urea [#]	
Description	Starter Kit	Stem Kit
Part Number	BP205S-DUNA	BP205X-DUNA
Modular Power Head	1	×
Rechargeable Battery	2.0Ah Li-ion	×
Cradle Charger	1	×
Easy Control Dispensing Gun	1	✓
Reinforced Hose	2m	2m
Stainless Steel Stem	1	✓
Bung Adaptor	Suits most 60/205 litre drums	
Compatible Fluids	Suitable for DEF/Urea, Engine Oil, Gear Oil, Hydraulic Oil (oils up to SAE140 viscosity), Automatic Transmission Fluid (ATF) and Coolant	

Type of Oil	Flow Rate	
,,		
Engine Oil	Up to 4.5 LPM	
High Vis Oil	Up to 2.4 LPM	
ATF	Up to 6 LPM	
Coolant	Up to 6.2 LPM	
DEF/Urea	Up to 7 LPM	

* The delivery rates depend on the type, viscosity and the temperature of the fluid. **SAE40 at 20°C, SAE140 at 20°C.

Length	2m	3m
Hose & Gun Set	BP-HG2	BP-HG3
Hose Assembly Kit	BP-HK2	ВР-НКЗ





BP20-PH **Power Head***

*Battery NOT included



IM012EB-01 **BOP** inline meter#



BPB-20AH 18V 2.0Ah Li-ion battery



BPC-A BOP Charger

Service Parts

BP-4K: BOP Seal kit for 60/205L DEF/UREA BP077S: Corded Dust Cap -Spare Kit BP60-AK: Bung Adapter Kit-BOP60

Applications:

Automotive, Truck and Buses, Farming Equipment, Textile Machinery, Construction and Earthmoving, Forklifts, Military Equipment (e.g. tanks, armoured vehicles), Mining Machinery, Aircraft, Trains



Flush with water after using Urea/DEF to prevent crystallization

Subject to Macnaught warranty terms and conditions, see www.macnaught.com.au/warranty