

LUBEMATE EL-SERIES ENCLOSED HOSE REELS

The Lubemate EL-Series Enclosed Hose Reels represent a relatively small, aesthetically neat hose containment solution for workshop applications. The reels are constructed of sturdy powder coated steel with stamped form for strength and fully enclosed spring and swivels for protection. Longevity is assured by equally robust multiple placement mounting brackets. The narrow form of the EL-Series Enclosed Hose Reels from Lubemate allow for the smallest possible wall or gantry space requirements.

SCAN FOR MORE INFORMATION



Sleek and durable enclosure
Designed for minimum profile

Powder-coated steel construction
For longevity and corrosion protection



High quality hose and fittings
Exceeds required standards

Long lasting spring
Fully enclosed and lubricated

APPLICATIONS

- Ideal for automotive workshops where reel banks are required. Either wall mounting or from overhead gantry structures.



Part Number	L-ELAW1015	L-ELAW1210	L-EL01210	L-ELG0615
Description	Air/Water Hose Reel 3/8" x 15m	Air/Water Hose Reel 1/2" x 10m	Oil Hose Reel 1/2" x 10m	Grease Hose Reel 1/4" x 15m
Application	Air/Water	Air/Water	Oil	Grease
Hose Size (ID)	3/8"	1/2"	1/2"	1/4"
Hose Length	15m	10m	10m	15m
Hose Material	NBR Rubber	NBR Rubber	S.A.E 100R1 Wire Braid	S.A.E 100R2 Wire Braid
Working Pressure	300 psi	300 psi	2320 psi	5800 psi
Max Temperature	80° C	80° C	100° C	100° C
Reel Inlet	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP
Hose Inlet	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205, Australia **Ph:** 1800 185 102 **Fax:** +61 2 9597 7773 **Email:** info@macnaught.com.au **Website:** macnaught.com