

NEW SHADOW R3 Series

Now available in a **Black** case

NEW

The R3 Series are industrial strength poly hose reels, built here in Australia. Manufactured in high impact polypropylene, our R3 hose reel is renowned for unmatched performance, reliability and durability. Built to blend in while standing out, the new **Shadow** elevates the aesthetics of your workshop without compromising the quality and performance you trust.



WATER

- RetractaFLEX Hybrid Polymer hose
- Maximum pressure 150 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
DR425K-03	12MM (1/2")	25M	GREEN	Black

APPLICATIONS:

Outdoor garden and horticulture



COMPRESSED AIR AND WATER

- Hybrid polymer hose for durability
- Maximum pressure 250 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
AW315K-01	10MM (3/8")	15M	BLUE	Black
AW320K-01	10MM (3/8")	20M	BLUE	Black
AW415K-01	12MM (1/2")	15M	BLUE	Black
AW420K-01	12MM (1/2")	20M	BLUE	Black

APPLICATIONS:

Suitable for use across most industries



OIL

- Wire reinforced rubber (SAE 100R17) hose
- Maximum pressure 1000 psi for reliability and performance.

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OMP415K-01	12MM (1/2")	15M	BLACK	Black

APPLICATIONS:

Suitable for use across most industries

GREASE

- High tensile steel braid reinforced rubber (SAE 100R2) hose
- Maximum working pressure 5000 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
GR215K-01	6MM (1/4")	15M	BLACK	Black



OXY/LPG

- Hybrid Twin gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 175 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OG215K-04	TWIN 5MM (3/16")	15M	BLUE/ ORANGE	Black

APPLICATIONS:

Suitable for use across most industries where Oxy/LPG is required



LPG

- Gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 200 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
LPG220K-04	5MM (3/16")	20M	ORANGE	Black

APPLICATIONS:

Suitable for use across most industries. E.g. Service Bays, Manufacturing, Construction, Welding Carts, Shipyards, Transport Service.



OXYACETYLENE

- Hybrid Twin gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 175 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OA215K-04	TWIN 5MM (3/16")	15M	BLUE/ RED	Black

APPLICATIONS:

Suitable for use across most industries where Oxy/Acet is required

GET IN TOUCH



AU CUSTOMER SERVICE
1800 185 102
orders@macnaught.com.au



NZ CUSTOMER SERVICE
0800 023 510
nzorders@macnaught.com.au



Find us on socials @macnaught