

# NEW SHADOW R3 Series

Now available in a **Black case**

**NEW**

The R3 Series are industrial strength poly hose reels, built here in Australia. Manufactured in high impact polypropylene, our R3 hose reel is renowned for unmatched performance, reliability and durability. Built to blend in while standing out, the new **Shadow** elevates the aesthetics of your workshop without compromising the quality and performance you trust.



## COMPRESSED AIR/WATER

- Hybrid polymer hose for durability
- Maximum pressure 250 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
AW315K-01	10MM (3/8")	15M	BLUE	Black
AW320K-01	10MM (3/8")	20M	BLUE	Black
AW415K-01	12MM (1/2")	15M	BLUE	Black
AW420K-01	12MM (1/2")	20M	BLUE	Black



### APPLICATIONS:

Suitable for use across most industries



## OIL

- Wire reinforced rubber (SAE 100R17) hose
- Maximum pressure 1000 psi for reliability and performance.

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OMP415K-01	10MM (3/8")	15M	BLACK	Black

### APPLICATIONS:

Suitable for use across most industries



## GREASE

- High tensile steel braid reinforced rubber (SAE 100R2) hose
- Maximum working pressure 5000 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
GR215K-01	6MM (1/4")	15M	BLACK	Black

### APPLICATIONS:

Suitable for use across most industries

## OXY/LPG

- Hybrid Twin gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 175 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OG215K-04	TWIN 5MM (3/16")	15M	BLUE/ ORANGE	Black

### APPLICATIONS:

Suitable for use across most industries where Oxy/LPG is required



## LPG

- Gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 200 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
LPG220K-04	5MM (3/16")	20M	ORANGE	Black

### APPLICATIONS:

Suitable for use across most industries. E.g. Service Bays, Manufacturing, Construction, Welding Carts, Shipyards, Transport Service.



## OXYACETYLENE

- Hybrid Twin gas hose made from reinforced rubber compliant to AS 1335
- Maximum working pressure 175 psi

PART NUMBER	HOSE SIZE (ID)	HOSE LENGTH	HOSE COLOUR	CASE COLOUR
OA215K-04	TWIN 5MM (3/16")	15M	BLUE/ RED	Black

### APPLICATIONS:

Suitable for use across most industries where Oxy/Acet is required

## GET IN TOUCH



AU CUSTOMER SERVICE  
**1800 185 102**  
orders@macnaught.com.au



NZ CUSTOMER SERVICE  
**0800 023 510**  
nzorders@macnaught.com.au



Find us on socials @macnaught