

## DESIGNED WITH WORKSHOP SAFETY IN MIND

Store your hoses and eliminate tripping hazards for good

- Highly durable Double Reinforced Rubber Hose
- Main spring made with Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully Serviceable
- Retracta Adjustable Control Return (RACR®) available as an option



### OXY / ACETYLENE OA215B-04

Hose Size: Twin 5mm (3/16")  
Hose Length: 15m  
Working Pressure: 175 psi  
Max Temperature: 80°C (176°F)  
Reel Inlet: Gas Thread UNF (M)  
Hose Outlet: Gas Thread UNF (F)



### OXY/LPG OG215K-04

Hose Size: Twin 5mm (3/16")  
Hose Length: 15m  
Working Pressure: 175 psi  
Max Temperature: 60°C (140°F)  
Reel Inlet: Gas Thread UNF (M)  
Hose Outlet: Gas Thread UNF (F)



### LPG LPG220K-04

Hose Size: 5mm (3/16")  
Hose Length: 20m  
Working Pressure: 200 psi  
Max Temperature: 60°C (140°F)  
Reel Inlet: Gas Thread UNF (M)  
Hose Outlet: Gas Thread UNF (F)



### ARGON ARG220D-04

Hose Size: Twin 5mm (3/16")  
Hose Length: 20m  
Working Pressure: 200 psi  
Max Temperature: 60°C (140°F)  
Reel Inlet: Gas Thread UNF (M)  
Hose Outlet: Gas Thread UNF (F)

Other Hose Reels Available from Retracta: Air | Air/Water | Water | Oil | Grease | Hot Wash | Cold Wash | Pressure Wash | Chemicals | F.R.A.S

## ACCESSORIES AVAILABLE



### MULTI POSITION LOCKING BRACKET RA-MLB

- Hold and lock hose reel at desired angle and direction
- Simple setup and easy to adjust



### BENCH MOUNT BRACKET BB200

- Compatible with all Retracta Welding Reels
- Easy to install