



Declaration of Compliance

EN10204:2004 type 2.2 for MX-Series Flow Meters

Macnaught Pty Limited
41 – 49 Henderson Street
Turrella NSW 2205 Sydney Australia
Postal Address PO Box 90
Arncliffe NSW Sydney Australia

ABN 66 000 075 785

T: + 61 2 9567 0401
F: + 61 2 9597 7773
W: www.macnaught.com.au

Macnaught Pty. Ltd. conducts a quality assurance system, certified as complying with AS/NZS ISO 9001:2015 by an accredited certification body.

This declaration of compliance (in accordance with EN 10204:2004 type 2.2) acknowledges that the MX- series flow meters, conform to all manufacturing specifications, assembly and test requirements set out in the relevant procedures and work instructions.

Hard copies of the following tests results/parameters are provided with each MX- series flow meter.

- K-Factor coefficient
- Hydraulic pressure drop
- Flow rate
- Accuracy of reading (%)
- Fluid temperature

Authorised signatory for and on behalf of Macnaught Pty Ltd

Signature :

Name : Marco Uccellani

Position : Engineering Manager

Date : 09/11/2020

Done at : Macnaught Pty Ltd; 41-49 Henderson St; Turrella NSW 2205; Australia

MATERIAL DECLARATIONS

316L Stainless Steel

	C	Si	Mn	P	S	Cr	Ni	Mo	N	Fe
	%	%	%	%	%	%	%	%	%	%
Min	-	-	-	-	-	16.0	10.0	2.0	-	-
Max	0.03	1.0	2.0	0.045	0.03	18.0	14.0	3.0	0.10	Rem.

AS2074 H6DM (Chill cast) Stainless Steel

(1) In free machining grades the Sulfur may be as high as 0.50%
(2) In free machining grades additional elements may be present

	C	Si	Mn	P	S ⁽¹⁾	Cr	Mo	Ni	Nb	Cu	V	N	Al	Fe
	%	%	%	%	%	%	%	%	%	%	%	%	%	%
Min	-	-	-	-	-	17.0	2.0	9.0	-	-	-	-	-	-
Max	0.03	1.5	2.0	0.04	0.04	21.0	3.0	13.0	-	-	-	-	-	Rem.

S1214 Bright Carbon Steel *S12L14

	C	Si	Mn	P	S	Pb*
	%	%	%	%	%	%
Min	-	-	0.8	0.04	0.25	0.15
Max	0.15	0.10	1.2	0.09	0.35	0.25

IC316F Stainless Steel*

*Investment Casting Institute

	C	Si	Mn	P	Cr	Mo	S	Fe
	%	%	%	%	%	%	%	%
Min	-	-	-	-	18.0	9.0	2.0	-
Max	0.08	2.0	1.50	0.40	21.0	12.0	3.0	0.04

CC601 T6 Aluminium Castings

	Si	Fe	Cu	Mn	Mg	Zn	Ti	Al
	%	%	%	%	%	%	%	%
Min	6.5	-	-	-	0.25	-	-	-
Max	7.5	0.2	0.05	0.05	0.35	0.05	0.2	Rem.

6061 T6 Aluminium

	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Al
	%	%	%	%	%	%	%	%	%
Min	0.4	-	0.15	-	0.8	0.04	-	-	-
Max	0.8	0.70	0.40	0.15	1.2	0.35	0.25	0.15	Rem.

EZDA 3 Zinc Die Casting Alloy

	Al	Mg	Cu	Pb	Fe	Cd	Sn	Si	Ni	In	Ti	Zn
	%	%	%	%	%	%	%	%	%	%	%	%
Min	3.9	0.04	-	-	-	-	-	-	-	-	-	-
Max	4.2	0.05	0.03	0.003	0.02	0.002	0.001	0.02	0.001	0.0005	0.001	Rem.

CA313 Aluminium Alloy - Castings

	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Sn	Pb	Ti	Al
	%	%	%	%	%	%	%	%	%	%	%	%
Min	7.5	-	3.0	-	-	-	-	-	-	-	-	-
Max	9.5	1.3	4.0	0.5	0.3	0.1	0.5	3.0	0.25	0.35	0.2	Rem.

385 Brass

	Cu	Pb	Zn
	%	%	%
Min	56.0	2.5	-
Max	60.0	4.5	Rem.

C83600 Bronze

(1) Minimum value may be calculated as copper and nickel.
(2) Nickel value includes cobalt

	Cu ⁽¹⁾	Al	Sb	Fe	Pb	Ni ⁽²⁾	P	Si	S	Sn	Zn
	%	%	%	%	%	%	%	%	%	%	%
Min	84.0	-	-	-	4.0	-	-	-	-	4.0	4.0
Max	86.0	0.005	0.25	0.3	6.0	1.0	0.05	0.005	0.08	6.0	6.0

Element definitions

Al	C	Cd	Cr	Cu	Fe	In	Mg	Mn	Mo	N	Nb	Ni	P	Pb	S	Sb	Si	Sn	Ti	V	Zn
Aluminium	Carbon	Cadmium	Chromium	Copper	Iron	Indium	Magnesium	Manganese	Molybdenum	Nitrogen	Niobium	Nickel	Phosphorus	Lead	Sulfur	Antimony	Silicon	Tin	Titanium	Vanadium	Zinc

(The currency of this document is not guaranteed when printed)
(End of document)