KY+XL LOAD & LUBE
SAFETY GREASE COUPLER

2 YEARS MACNAUGHT WARRANTY*

The innovative new KYPLUSXL long grease coupler is a standard game changer in equipment maintenance. In fact, for any high grease application, KYPLUSXL delivers improved access, productivity and safety through a new patented design. The "superior interior" is the KYPLUSXL difference. KYPLUSXL is more versatile, reliable, leak free and easy to use. The KYPLUSXL nose is 2.5"(64mm), making it longer than the KY+ 1.3"(34mm).

KY+ LOAD & LUBE SAFETY GREASE COUPLER XL

Up to **10,000 psi**

NEW GREASE COUPLER

PATENT • APPROVED

MANUFACTURED IN AUSTRALIA

GOOD DESIGN AWARD® WINNER

Internal Pressure Relief

For greater safety and minimise grease spurts.

Quick & easy release mechanism

Patent approved smart release mechanism enables effortless one handed release & pull up to 10,000psi.

Original KY floating jaw

Unique floating jaw operation creates a powerful grip as pressure builds to enhance performance.

2.5" (64mm)

KYPLUSXL-01

Superior safety

Smart release mechanism features an internal bleeding system for soft pressure relief and safe disconnect of the coupler up to 10,000 psi.

Compact design

The compact body of the KY+XL makes it easier to get into tight spaces.

FEATURES & BENEFITS

- Patent Approved internal pressure relief mechanism for easy disconnect under pressure and superior safety
- Compact design for greater accessibility
- Original Floating jaw design for leak free grip
- Quick & easy release mechanism enabling one handed operation Load & Lube!

TECHNICAL SPECIFICATION

- Built-in hydraulic pressure relief
- 1/8" (F) inlet (BSP/NPT) & M10X1 (F) inlet threads available
- Maximum working pressure: 10,000psi (68,900kPa)
- Dimensions: 101mm x 15mm

KY+XL LOAD & LUBE
SAFETY GREASE COUPLER

2 YEARS MACNAUGHT WARRANTY*

BLISTER PACK

KYPLUSXL-01 (1/8" BSP)

KYPLUSXL-02 (1/8" NPT)

KYPLUSXL-03 (M10X1)

COUNTER DISPLAY PACK

KYPLUSXL-01-10 (BSP)
KYPLUSXL-02-10 (NPT)
KYPLUSXL-03-10 (M10X1)

KY+ LOAD & LUBE SAFETY GREASE COUPLER XL

1. LOAD

Pull back and then release fingers

1. LOAD
2. LUBE

Hold coupler extension and engage nipple - Ready to Lube

1. LOAD
2. LUBE
3. RELEASE

To disengage - pull back and release fingers

1. LOAD
2. LUBE
3. RELEASE
4. PULL

Hold coupler extension and disengage from nipple

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	THREAD TYPE	COUPLER QUANTITIES
KYPLUSXL-01	KYPLUSXL Grease Coupler - BSP	1/8" BSP (F)	1
KYPLUSXL-02	KYPLUSXL Grease Coupler - NPT	1/8" NPT (F)	
KYPLUSXL-03	KYPLUSXL Grease Coupler - M10X1	M10X1 (F)	
KYPLUSXL-01-10	KYPLUSXL Grease Coupler - BSP (Counter Display - 10's pack)	1/8" BSP (F)	10 (in blister packs)
KYPLUSXL-02-10	KYPLUSXL Grease Coupler - NPT (Counter Display - 10's pack)	1/8" NPT (F)	
KYPLUSXL-03-10	KYPLUSXL Grease Coupler - M10X1 (Counter Display - 10's pack)	M10X1 (F)	

Built to last since 1948.

PATENT APPROVED

KY+ LOAD & LUBE SAFETY GREASE COUPLER XL