

180° Galvanised steel swivel mounting bracket

UV Stabilised & impact resistant poly case

TECHNICAL SPECIFICATIONS

Twin gas hose made from reinforced rubber

compliant to AS 1335

ProGlide high wear

resistant mouth

Case Colour	Black	
Part Number	OG215K-04	
Hose Size (ID)	Twin 5mm (3/16")	
Hose Length	15m	
Hose Colour	Orange 🔿	Blue 🔿
Reel Inlet	Gas Thread UNF (M)	
Hose Outlet	Gas Thread UNF (F)	
Hose Material	Reinforced Rubber (AS 1335)	
Working Pressure	175 psi	
Max Temperature	60°C	

Applications:

Suitable for use in all industries where Oxy/LPG is required.

FEATURES AND BENEFITS

Designed	d and manufactured in Australia.
ProGlide	e high wear resistant mouth.
Advance	d spring technology.
180° Gal	Ivanised steel swivel mounting bracket.
Light we	ight & easy to handle.
Twin gas 1335.	hose made from reinforced rubber compliant to AS
Maximu	m working pressure 175 psi.
Fully ser	viceable.

<u>ETRACI</u>

PACKAGE INCLUDES

Hose Reel - OXYGEN/LPG

Locking Bracket (Locks reel in position at 90°)

Fixing hardware not included.

180° FREEDOM OF ROTATION CONTROL OF ROTAT

RETRACTA R3 SERIES OXYGEN/LPG HOSE REELS

outstanding support in the welding environment specifically to handle LPG.



The R3 Series are industrial strength poly hose reels, built here in Australia. Manufactured in high impact polypropylene, our legendary R3 hose reel is renowned for unmatched performance, reliability and durability. The LPG reel is supplied with a 20m hose, made from reinforced rubber compliant to AS 1335 to ensure



macnaught

