

Hi- Flow Diesel Automatic Nozzle

L-ANHF



The Lubemate Automatic Diesel Nozzle is built for precision, durability, and efficiency. Designed for high-flow diesel dispensing, this heavy-duty automatic nozzle ensures seamless fuel transfer while preventing overflows with its auto shut-off feature. Designed for tough environments, the L-ANHF delivers reliable performance, making refueling faster, safer, and more efficient.

Aluminium Body
Lightweight yet durable and strong

Automatic Shut-off
Prevent overfills & wastage

Trigger Lock
Allows flow control in 3 positions

Inlet Strainer
Prevent debris from entering the nozzle




TECHNICAL SPECIFICATIONS

- Flow Rate: up to 120 LPM
- Inlet: 1" BSPP (F)
- Outlet Spout Diameter: 30 mm
- Suitable Fluids: Diesel & Kerosene
- Maximum Working Pressure: 50 PSI

RECOMMENDED FOR USE WITH



L-FS25
(Straight Swivel 1")



L-DPFS25
(Dual Plane Swivel 1")

RANGE OF 1" DIESEL NOZZLES

L-FNMD	Manual Diesel Nozzle 60 LPM
L-SFNAD120	Diesel Nozzle Auto - Slim Profile - 120 LPM
L-FNAD120M	Diesel Automatic Metered Nozzle - 120 LPM

APPLICATIONS:

- Automotive Workshops
- Trucks & Buses
- Mining
- Agriculture
- Construction Machinery
- Earthmoving Equipments
- Industrial
- Marine

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. **AU:** Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. **Ph:** 1800 185 102 **Fax:** +61 2 9597 7773 **Email:** info@macnaught.com.au **Website:** macnaught.com.
NZ: Macnaught NZ 2/1 Hautu Drive, Wiri Auckland Macnaught Pty Ltd **Ph:** 0800 023 510 **Email:** nzorders@macnaught.com.au