

Diesel Automatic Metered Nozzle L-FNAD120M



The Lubemate Automatic Diesel Nozzle combines precision, durability, and user-friendly design for reliable diesel dispensing. Built with a high-flow capacity, this nozzle ensures efficient and seamless diesel transfer while its auto shut-off feature prevents overfills, offering enhanced safety during fueling operations. The integrated digital flowmeter provides accurate and real-time measurements, making it easier to track and manage diesel usage. The nozzle features an auto-sleep function that activates after 40 seconds of inactivity, extending battery life.

Automatic Shut-off

Prevent overspills & wastage

Aluminium Body

Lightweight yet durable and strong

Trigger Lock

Allows flow control in 3 positions

Inlet Strainer

Prevent debris from entering the nozzle



Digital Flowmeter

- 5 digit resettable meter
- Accuracy: $\pm 1\%$
- Flowmeter Range: 10 - 120 LPM
- Measurement Units :
Litres, Gallons, Quarts and Pints
- Batteries Included

TECHNICAL SPECIFICATIONS

- Flow Rate: up to 120 LPM
- Inlet: 1" BSPP (F)
- Outlet Spout Diameter: 30 mm
- Suitable Fluids: Diesel & Kerosene
- Temp. Range: -25°C to 55°C
- Maximum Working Pressure: 50 PSI

RECOMMENDED FOR USE WITH



Straight Swivel
1" (L-FS25)



Dual Plane Swivel
1" (L-DPFS25)

Range of 1" Fuel Nozzles

L-FNMD	Manual Diesel Nozzle 60 LPM
L-ANHF	Hi-Flo Diesel Nozzle Auto 120 LPM
L-SFNAD120	Auto Diesel Nozzle - Slim Profile - 120 LPM

Applications:

- Automotive Workshops
- Mining
- Construction Machinery
- Industrial
- Trucks & Buses
- Agriculture
- Earthmoving Equipments
- Marine

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations