

Automatic Diesel Nozzle Premium L-FNADP



The Lubemate Premium Automatic Diesel Nozzle is designed for efficient diesel fuel delivery, with a flow capacity of up to 60L/min. Designed for durability and ease of use, this premium nozzle is built to withstand demanding applications while ensuring user comfort. It is equipped with a positioning control device that automatically shuts off the nozzle if it falls from a vehicle or is tipped upward, minimizing spillage and enhancing safety.

Automatic Shut-off
Prevent overfills & wastage

Position Control Device
Auto shut off when displaced and tipped up

Trigger Lock
Allows flow control in 3 positions

Aluminium Body
Lightweight yet durable and strong




TECHNICAL SPECIFICATIONS

- Flow Rate: up to 60 LPM
- Inlet: 3/4" BSPT (F)
- Outlet Spout Diameter: 15/16"
- Suitable Fluids: Diesel & Kerosene
- Maximum Working Pressure: 50 PSI

RECOMMENDED FOR USE WITH



L-FS19
(Straight Swivel 3/4")



L-DPFS19
(Dual Plane Swivel 3/4")

RANGE OF 3/4" DIESEL NOZZLES

L-FNAD	Automatic Diesel Nozzle 60 LPM (BSPT)
L-FNAD-P	Automatic Diesel Nozzle 60 LPM (BSPP)
L-FNAD-P	Auto Diesel Nozzle Premium 60 LPM (BSPP)
L-SFNAD60	Diesel Nozzle Auto - Slim Profile - 60 LPM

APPLICATIONS:

- Automotive Workshops
- Trucks & Buses
- Mining
- Agriculture
- Construction Machinery
- Earthmoving Equipments
- Industrial
- Marine

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations