

Manual Diesel Nozzle

L-FNMD



The Lubemate Manual Diesel Nozzle is designed for durability and ease of use. Featuring a lightweight yet rugged construction, it provides smooth, controlled fuel flow for efficient diesel dispensing. Built to withstand tough conditions, this high-quality manual nozzle offers reliable performance for various diesel fueling applications.

Aluminium Body
Lightweight yet durable and strong

Hanging Hook
Easy Storage when not in use

Trigger Lock (Removable)
Allows flow control in 2 positions

Swivelled Threaded Inlet
Eases installation and prevents hose twisting



TECHNICAL SPECIFICATIONS

- Flow Rate: up to 60 LPM
- Nozzle Type : Manual
- Inlet: 1" BSPP (F)
- Outlet Spout Diameter: 15/16"
- Suitable Fluids: Diesel & Kerosene
- Maximum Working Pressure: 50 PSI

RECOMMENDED FOR USE WITH



L-FS25
(Straight Swivel 1")



L-DPFS25
(Dual Plane Swivel 1")

RANGE OF 1" DIESEL NOZZLES

L-ANHF	Hi-Flow Diesel Automatic Nozzle - 120 LPM
L-SFNAD120	Diesel Nozzle Auto - Slim Profile - 120 LPM
L-FNAD120M	Diesel Automatic Metered Nozzle - 120 LPM

APPLICATIONS:

- Automotive Workshops
- Mining
- Construction Machinery
- Industrial
- Trucks & Buses
- Agriculture
- Earthmoving Equipments
- Marine

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. **AU:** Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. **Ph:** 1800 185 102 **Fax:** +61 2 9597 7773 **Email:** info@macnaught.com.au **Website:** macnaught.com.
NZ: Macnaught NZ 2/1 Hautu Drive, Wiri Auckland Macnaught Pty Ltd **Ph:** 0800 023 510 **Email:** nzorders@macnaught.com.au