

UREA/DEF Metered Auto Nozzle

L-PANM



The Lubemate Automatic Urea/DEF Nozzle combines precision, durability and user-friendly design for reliable dispensing. This nozzle ensures efficient and seamless Urea/DEF transfer while its auto shut-off feature prevents overfills, offering enhanced safety during refilling operations. The integrated digital flowmeter provides accurate and real-time measurements, making it easier to track and manage Urea/DEF usage. The nozzle features an auto-sleep function that activates after 40 seconds of inactivity, extending battery life.



TECHNICAL SPECIFICATIONS

- Flow Rate: up to 30 LPM
- Inlet: 3/4" with barb
- Outlet Spout Diameter: 19 mm
- Suitable Fluids: Urea / DEF
- Temp. Range: -10°C to 55°C
- Maximum Working Pressure: 50 PSI

RECOMMENDED FOR USE WITH



LH198B (EPDM Urea/DEF Hose 3/4" - 8 meters)

• Trucks &

BusesAgriculture

• Marine

Earthmoving

Equipments

APPLICATIONS:Automotive

Workshops

Construction

Machinery

Industrial

• Mining

RANGE OF UREA/DEF NOZZLES

L-SSANM	Adblue/Def SS Auto Nozzle W/ Magnetic Adaptor & Swivel
L-PAN	Adblue/Def Poly Auto Nozzle
L-PMN	Adblue/Def Poly Manual Nozzle

 $\ensuremath{^*\text{This}}$ nozzle is not intended for use at service stations (servo) / fuel stations or gas stations



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. AU: Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com. NZ: Macnaught NZ 2/1 Hautu Drive, Wiri Auckland Macnaught Pty Ltd Ph: 0800 023 510 Email:nzorders@macnaught.com.au

macnaught.com