

Diesel Nozzle Auto - Slim Profile

L-SFNAD120



The Lubemate Slim Profile Automatic Diesel Nozzle is built for reliable, high-performance fuel dispensing. Designed for durability and ease of use, it features a lightweight yet robust construction for effortless handling. Built with a high-flow capacity, this nozzle ensures efficient and seamless diesel transfer while its auto shut-off feature prevents overfills, offering enhanced safety during fueling operations. Perfect for demanding diesel applications, this slim profile diesel nozzle delivers efficiency and dependability.

Aluminium Body

Lightweight yet durable and strong

Equipped with a Swivel

Eases installation and prevents hose twisting



Automatic Shut-off

Prevent overspills & wastage

Trigger Lock

Allows flow control in 2 positions

TECHNICAL SPECIFICATIONS

- Flow Rate: up to 120 LPM
- Inlet: 1" BSPP (F)
- Outlet Spout Diameter: 31mm
- Suitable Fluids: Diesel & Kerosene
- Maximum Working Pressure: 50 PSI

RANGE OF 1" FUEL NOZZLES

L-FNMD	Manual Diesel Nozzle 60 LPM
L-ANHF	Hi-Flo Diesel Nozzle Auto 120 LPM
L-FNAD120M	Diesel Automatic Metered Nozzle - 120 LPM

APPLICATIONS:

- Automotive Workshops
- Trucks & Buses
- Mining
- Agriculture
- Construction Machinery
- Earthmoving Equipments
- Marine
- Industrial

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. AU: Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com. NZ: Macnaught NZ 2/1 Hautu Drive, Wiri Auckland Macnaught Pty Ltd Ph: 0800 023 510 Email: nzorders@macnaught.com.au