



Macnaught Diesel Tanks

Statement of Suitability

Macnaught Pty. Ltd. conducts a quality assurance system, certified as complying with AS/NZS ISO 9001:2015 by an accredited certification body.

Material used in making Macnaught Diesel Tanks are tested to meet the mechanical and chemical resistance requirements of International Regulations ECE R34.01 Annex 5 Section 5.0 and European Directive 2000/8/EC which are specifically designed for Roto-moulding process.

Anti-static hoses are supplied with all the tanks, in addition to it tanks above 800 Litres capacity are supplied in with anti-static lead that exceeds the requirements of AS1940-2004 and AS2809.2-2008.

Macnaught Diesel Tanks are fitted with Filler caps and vents that comply to AS1940-2004 standards.

Diesel fuel is **not** classified as

1. Dangerous Good as per the Australian Code for Transport of Dangerous Goods by Road and Rail. (According to fuel company MSDS)
2. Flammable Liquid in Australia; but classified as 'Combustible Liquid C1' (According to fuel company MSDS)

Note: AS NZS 2906-2001 requirements are not applicable to Macnaught Diesel Tanks as the tank capacity exceeds 25 Litres.

WARNING

MACNAUGHT DIESEL TANKS ARE CLASSIFIED AS 'MINOR STORAGE' FOR CLASS C1 COMBUSTIBLE LIQUIDS WHEN OPERATED CORRECTLY IN COMPLIANCE WITH AS1940-2004.

OPERATORS/USERS SHOULD FAMILIARISE THEMSELVES WITH THE REQUIREMENTS OF as 1940-2004 STANDARDS **BEFORE OPERATING.**